

Material Safety Data Sheet

U.S. Department of Labor

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

Identity: (As used on Label and List)

RepCon H-350

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name

SpecChem

Emergency Telephone Number

(800) 424-9300

Address (Number, Street, City, State, and ZIP Code)

Telephone Number for Information

(913) 371-8700

444-B Richmond Ave

Date Prepared

3/27/07

Kansas City KS 66101

Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components ; Common Name(s)

OSHA PEL

ACGIH TLV

(Specific Chemical Identity)

65997-15-1 Portland Cement

5 mg/m³

10 mg/m³

14808-60-7 Silica or Natural Sand

0.1 mg/m³

.01 mg/m³

NIOSH RECOMMENDS - A permissible exposure limit of 50 micrograms respirable free silica per cubic meter of air averaged over a normal work week of 40 hours.

Section III - Physical/Chemical Characteristics

Boiling Point

N/A

Specific Gravity

(H₂O = 1)

N/A

Vapor Pressure (mm Hg.)

N/A

Melting Point

N/A

Vapor Density (AIR = 1)

N/A

Evaporation Rate

(Butyl Acetate = 1)

N/A

Solubility in Water Negligible

Appearance and Odor

Gray appearance - no odor

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)

N/A

Flammable Lmt

N/A

LEL

N/A

UEL

N/A

Extinguishing Media

N/A

Special Fire Fighting Procedures

Non-combustible; non-explosive

Unusual Fire and Explosion Hazards

N/A

Section V - Reactivity Data			
Stability:		Conditions to Avoid:	
Unstable		Silica Sand is capable of dissolving in hydro-flouric acid &	
Stable	X	producing a gas - Silicon Tetrafluori	
Incompatibility (<i>Materials to Avoid</i>) Not incompatible with most materials			
Hazardous Decomposition or Byproducts			
Hazardous Polymerization:		Conditions to Avoid:	
May Occur			
X	Will Not Occur	Upon direct contact with water, material will harden.	

Section VI - Health Hazard Data			
Route(s) of Entry:	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (<i>Acute and Chronic</i>) MSHA & OSHA Classification as nuisance dust			
Carcinogenicity:	NTP? Yes	IARC Monographs? Yes	OSHA Regulated? No
Signs and Symptoms of Exposure skin dryness; alkali burns; nuisance resulting in eye & respiratory systems, shortness of breath, reduced pulmonary function.			
Medical Conditions Generally Aggravated by Exposure Those with sensitive skin or with pulmonary/respiratory disease such as asthma & bronchitis should be precluded from exposure.			
Emergency and First Aid Procedures Repeatedly flood eyes with clean water. Exposed skin areas should be washed with soap & water; for inhalation get fresh air. Get medical attention.			

Section VII - Precautions for Safe Handling and Use	
Steps to Be Taken in Case Material Is Released or Spilled With adequate ventilation, clean-up with as little as dust as possible and place into a closed container for disposal or use.	
Waste Disposal Method In accordance with Federal, State and Local Regulations may be treated as common waste.	
Precautions to Be Taken in Handling and Storing In accordance with Federal, State and Local Regulations may be treated as common waste.	
Other Precautions Keep dry whenever possible.	

Section VIII - Control Measures	
Respiratory Protections (<i>Specify Type</i>) NIOSH, MSHA, or OSHA Approved respirator	
Ventilation	
Local Exhaust to control dust if necessary	Special
Mechanical (General)	Other
Protective Gloves Recommended	Eye Protection Recommended
Other Protective Clothing or Equipment: Use impermeable protective clothing. Prevent skin contact with contaminated clothing.	
Work/Hygienic Practices Wash clothing before re-use. Thoroughly clean contaminated clothing.	

Section IX - Special Precaution**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:**

KEEP MATERIAL DRY UNTIL USED. HIGH HUMIDITY OR MOISTURE WILL CAUSE PREMATURE HARDENING OF MATERIAL.

OTHER PRECAUTIONS:

DO NOT TAKE INTERNALLY. WASH HANDS AFTER USE AND BEFORE SMOKING OR EATING, EXPOSURE TO AIRBORNE CRYSTALLINE SILICA SHALL NOT EXCEED 8 HOURS A DAY, SEE 29CFR 1910.1000 TABLE Z-3. SEE ALSO OSHA 29 CFR.1910.134; ANSI Z.88.2; NIOSH POCKET GUIDE TO CHEMICAL HAZARD

Section X - SARA Title II Information

This product contains the following substances subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: **N/A**

Name			
CAS#			
PC WEIGHT			

Section XI - D.O.T. Regulations (Transportation)

Hazard Class	N/A
ID Number	N/A
Packing Group	III
Proper shipping name	Not regulated by DOT
Label	N/A
US Domestic Ground Shipments	Not regulated by DOT
US Domestic Ground Shipments-Non-Bulk (in containers 119 gal or less)	Not regulated by DOT
Cross Border transport (ADR/RID)	N/A
ADR/RID Class	
Danger Code (Kemler)	
UN Number	
Label	
Packing Group	
Description	
Marine Transport (IMDG)	N/A
IMDG Class	
UN Number	
Label	
Packing Group	
EMS Number	
Marine pollutant	No
Proper shipping name	
Air Transport (ICAO-TI and IATA-DGR)	N/A
ICAO/IATA class	
UN Number	
Label	
Packing Group	
Proper shipping name	

Disclaimer and Limitation of Liability

The information and recommendations contained herein were obtained from sources we believe to be accurate and reliable as of the date revised. However, SpecChem does not warrant or guarantee their accuracy or reliability, and shall not be liable for any loss or damage arising out of the use thereof. The information and recommendations are offered for the user's consideration and examination and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use.